

1. Product Identification

Product Name: PTFE Suspension Molding Powder PF-S62A

Chemical Name: Polytetrafluoroethylene (PTFE)

CAS No.: 9002-84-0

Polymerization Method: Suspension Polymerization

Processing Method: Compression Molding

PF-S62A is a fine particle PTFE molding grade with high flex resistance, good weldability and low metal ion extractables, designed for thin-walled flexing components.

2. Typical Applications

- Diaphragms
- Bellows
- Flexible molded components
- Semiconductor and 5G components
- Electrical insulation parts

Final application validation remains the responsibility of the processor/end user.

3. Typical Properties Of PTFE Suspension Molding Powder PF-S62A (Data not for specification purposes)

Property	Unit	Typical Value
Appearance	—	White Powder
Tensile Strength $\geq$	MPa	30
Elongation at Break $\geq$	%	350
Particle Size	μm	20 – 30
Bulk Density	g/L	300 – 500
Moisture Content $\leq$	%	0.030
Standard Specific Gravity	—	2.130 – 2.180
Flex Life (0.4 mm film, 23°C) $\geq$	$\times 10^4$ cycles	600
Permanent Compression Set (23°C, 14 MPa, 24 h) $\leq$	%	6.0
Dielectric Strength $\geq$	MV/m	100

4. Key Performance Characteristics

- Excellent thermal resistance (continuous use up to 260°C)
- Outstanding chemical resistance
- High flex life for thin films and bellows
- Good dielectric performance
- Good weldability and low metal ion extractables

5. Processing Recommendations

Recommended Processing Method: **Compression Molding**

Typical molding procedure:

- Cold preforming
- Sintering above melting temperature (~327°C)
- Controlled cooling

Processing parameters should be optimized by the converter based on final application requirements.

6. Packaging

- Double-layer polyethylene inner bag
- Rigid outer drum
- Net weight: 20 kg per drum
- Each drum supplied with batch identification and certificate of analysis

7. Storage And Handling

- Store in a clean, dry, well-ventilated warehouse
- Protect from moisture and contamination
- Avoid heavy vibration and mechanical impact during transport
- Not classified as dangerous goods under ADR, IMDG, or IATA

8. Regulatory Information (EU Compliance Statement)

- The product does not intentionally contain SVHC substances above 0.1% (w/w) as defined under REACH (EC) No 1907/2006.
- Compliant with RoHS Directive 2011/65/EU (as amended).
- Not classified as hazardous under CLP Regulation (EC) No 1272/2008.
- Safety Data Sheet available upon request.

Formal Declarations of Compliance can be provided upon request.

QUZHOU DFS CHEM CO., LTD.

LOCATION

NO 288, Qinjiang East Road, Kecheng
Quzhou, Zhejiang, China

CONTACT US

Phone: +86 570 2969501
Email: info@peflon.com