Product Overview

Product: PF-8P02E is a kind of polyvinylidene fluoride,which has high molecular weight ,viscosity and bonding,easy film-forming.

Typical Applications: It is typically used to lithium battery electrodes binder materials.

Availability: The package is packed in ton bags. The net content of ton bags is 190kg or 250kg.

TYPICAL PROPERTIES OF PVDF Powder PF-8P02E (Data not for specification purposes)

Properties	Test Method	Unit	PF-8P02E
Appearance			White powder
Odor			Without
Viscosity	25°C 0.07g/gNMP	mpa・s	2000-5000
MFR	GB/T 3682	g/10min	5 -15 (2.16 kg)
Relative density	GB/T 1033		1.75-1.79
Melting point	GB/T 28724	°C	156-165
Thermal decomposition,≥	GB/T 33047	°C	380
moisture,≤	GB/T 6284	%	0.10

CERTIFICATION

- SGS Certification
- ROHS Certification
- REACH Certification
- SVHC Certification

Attention

Keep PVDF Powder PF-8P02E from high temperature to prevent toxic gas releasing at the temperature above 350℃.

PACKAGE, TRANSPORTATION AND STORAGE

1.The package is packed in ton bags. The net content of ton bags is 155kg,190kg or 250kg.

2.The product should be transported as non-dangerous product, avoiding heat, moisture and strong shock.

3. Stored in clean and dry places, and temperature range is 5-30℃. Avoid contamination from dust and moisture.

QUZHOU DFS CHEM CO., LTD.

LOCATION

NO 288, Qinjiang East Road, Kecheng
Quzhou, Zhejiang, China

CONTACT US

Phone: +86 570 2969501
Email: info@peflon.com