PVDF Powder PF-8P03 is the homopolymer of vinylidene fluoride for coating. PF-8P03 have fine chemistry corrosion resistance, fine ultraviolet ray and the high energy radiativity resistance.

Product Overview

Product: PF-8P03 have fine chemistry corrosion resistance, fine ultraviolet ray and the high energy radiativity resistance. PFOA Free.

Typical Applications: It is typically used to produce fluorocarbon coating as fluorocarbon resin.

Availability: The package is packed in ton bags. The net content of ton bags is 190kg or 250kg.

TYPICAL PROPERTIES OF PVDF Powder PF-8P03 (Data not for specification purposes)

Properties	Test Method	Unit	PF-8P03
Appearance			White powder
Odor			Without
Scattered fineness,≤	GB/T 6753.1-2007	μm	25
Melting Index	GB/T 3682	g/10min	5 -15 (2.16 kg)
Relative density	GB/T 1033		1.75-1.79
Melting point	GB/T 28724	°C	165-175
Thermal decomposition,≥	GB/T 33047	°C	380
moisture,≤	GB/T 6284	%	0.10

CERTIFICATION

- SGS Certification
- ROHS Certification
- REACH Certification
- SVHC Certification

Attention

Keep PVDF Powder PF-8P03 from high temperature to prevent toxic gas releasing at the temperature above 350℃.

PACKAGE, TRANSPORTATION AND STORAGE

1.The package is packed in ton bags. The net content of ton bags is 155kg,190kg or 250kg.

2.The product should be transported as non-dangerous product, avoiding heat, moisture and strong shock.

3. Stored in clean and dry places, and temperature range is 5-30℃. Avoid contamination from dust and moisture.

QUZHOU DFS CHEM CO., LTD.

LOCATION

NO 288, Qinjiang East Road, Kecheng
Quzhou, Zhejiang, China

CONTACT US

Phone: +86 570 2969501
Email: info@peflon.com