

## Product Overview

**Product:** PF-8P62 is the homopolymer of vinylidene fluoride with fine mechanical strength and toughness.

**Typical Applications:** It is typically used to produce PVDF products by injection, extrusion and other processing technology.

**Availability:** The package is packed in ton bags. The net content of ton bags is 190kg or 250kg.

### TYPICAL PROPERTIES OF PVDF Powder PF-8P62 (Data not for specification purposes)

---

Properties	Test Method	Unit	PF-8P62
Appearance			Pellet/Powder
MFR	GB/T 3682	g/10min	7.1-14.0
Melting point	GB/T 28724	°C	165-175
Thermal decomposition,≥	GB/T 33047	°C	380
Tensile Strength,≥	GB/T 1040	Mpa	35.0
Elongation at break,≥	GB/T 1040	%	25.0
Standard relative density	GB/T 1033		1.75-1.79
Hardness	GB/T 2411	Shore D	70-80

## CERTIFICATION

---

- SGS Certification
- ROHS Certification
- REACH Certification
- SVHC Certification

### Attention

---

Keep PVDF Powder PF-8P62 from high temperature to prevent toxic gas releasing at the temperature above 350°C .

## PACKAGE, TRANSPORTATION AND STORAGE

---

- 1.The package is packed in ton bags. The net content of ton bags is 155kg,190kg or 250kg.
- 2.The product should be transported as non-dangerous product, avoiding heat, moisture and strong shock.
3. Stored in clean and dry places, and temperature range is 5-30°C. Avoid contamination from dust and moisture.

---

## QUZHOU DFS CHEM CO., LTD.

### LOCATION

NO 95, Changqian Road, Kecheng  
Quzhou, Zhejiang, China

### CONTACT US

Phone: +86 13957007557  
Email: [info@peflon.com](mailto:info@peflon.com)